

Mabanol Delta 2T-R

Semi-Synthetic Two Stroke Engine Oil

Application

Mabanol Delta 2T-R is recommended in accordance with manufacturer's instructions for mixing ratios of up to 1:50 and for separate lubrication (autolube systems). This two-stroke engine oil complies with the highest specifications for both the Asian and the European market.

Properties

Mabanol Delta 2T-R is a self-mixing semi-synthetic low-smoke two-stroke motor oil. Mineral oils derived from the most modern refinery techniques, synthetic components and special additives guarantee optimal lubricity and a high degree of engine cleanliness. Deposit build-up in the combustion chamber and the exhaust system are prevented, smoke development is substantially reduced.

Specifications

- ISO L-EGD
- API TC
- JASO FC
- TISI

Recommended for

- Husqvarna Chainsaw

Data

	Test method	Unit	Value
Density at 15°C	DIN 51 757	g/cm ³	0,872
Kin. Viscosity at 40°C	DIN EN ISO 3104	mm ² /s	67,5
Kin. Viscosity at 100°C	DIN EN ISO 3104	mm ² /s	9,53
Viscosity Index (VI)	DIN ISO 2909		121
Flash point PM	DIN EN ISO 2719	°C	123
Pourpoint	DIN ISO 3016	°C	-33
Total base number	DIN ISO 3771	mg KOH/g	1,1

Updated in January 2019

The above values may vary within the commercial limits.

Customs Tariff No.: 2710 1981